



MODELO	Interior		HEC25TF2-IN	HEC35TF2-IN	HEC50TF2-IN
	Exterior		HSU-09TK1/R32(DB)-OUT	HSU-12TK1/R32(DB)-OUT	HSU-18TK1/R32(DB)-OUT
EAN	Interior		6924362767842	6924362767873	6924362767828
	Exterior		6924362767422	6924362767446	6924362743631
Capacidad nominal	Frío/Calor	kW	2.6/2.8	3.5/3.6	5.0/5.2
Consumo nominal	Frío/Calor	kW	0.80/0.75	1.24/1.05	1.46/1.40
SEER/SCOP	Refrigeración/Calefacción		6.1/4.0	6.1/4.0	6.1/4.0
Clase energ.	Refrigeración/Calefacción		A++/A+	A++/A+	A++/A+
Caudal aire	Int./Ext.	m3/min	500/2100	550/2100	900/2500
Presión sonora	Interior	dBA (mínima)	18	19	28
	Exterior	dBA	49	50	53
Dimensiones	Interior	An./Fon./Al. (mm)	708/190/263	820/195/280	1008/225/318
	Exterior	An./Fon./Al. (mm)	700/245/544	700/245/544	800/275/553
Peso	Interior	Neto/Bruto (kg)	7.4/8.8	8.2/10.5	11.6/14.4
	Exterior	Neto/Bruto (kg)	22.6/25.1	22.8/25.3	32.7/36.5
Cantidad ref.	R32	g/m	460	500	900
Conexiones	Líquido	mm (pulg.)	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")
	Gas	mm (pulg.)	9.52 (3/8")	9.52 (3/8")	12.7 (1/2")
Rango de temperatura	Frío	°C	(-10°C) ~ (43°C)		
	Calor	°C	(-15°C) ~ (24°C)		
Longitud máxima tubería	m		15	15	25
Diferencia de altura máx.	m		10	10	15
Metros precarga/Carga adicional	m-g/m		5-20	5-20	7-20
PVR (sin IVA) Unidad interior + Unidad exterior			388 €	407 €	796 €